

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An imaging system, comprising:
  - a two-dimensional array of pixels;
  - an input device that includes a pixel device which further includes a sensor that provides an electronic signal that represents a multi-color image or an x-ray an image to the two-dimensional array of pixels, the sensor being a multi-color sensor or an x-ray sensor;
  - at least one transistor connected to the sensor;
  - a first capacitor that ~~stores the electronic signal provided by~~ is selectively connected to the sensor;
  - a second capacitor that ~~stores the electronic signal provided by~~ is selectively connected to the sensor; and
  - a controller that selectively stores the entirety of the electronic signal provided by the sensor in either the first capacitor or the second capacitor.
2. (Previously Presented) The imaging system according to claim 1, the pixel device further comprising:
  - a plurality of transistors and at least two control signals, one of the at least two control signals controlling one of the plurality of transistors so that the electronic signal is stored in the first capacitor, and the other one of the at least two control signals controlling another one of the plurality of transistors so that the electronic signal is stored in the second capacitor.
3. (Original) The imaging system according to claim 2, wherein the first capacitor is independently active for greater than 10 microseconds.

4. (Withdrawn) The imaging system according to claim 2, the pixel device further comprising a third and fourth capacitor connected to the sensor.

5. (Withdrawn) The imaging system according to claim 4, the pixel device further comprising:

a plurality of control signals, at least one of the at least plurality of control signals controlling a third one of the plurality of transistors so that the electronic signal is stored in the third capacitor, and at least another one of the plurality of control signals controlling a fourth one of the plurality of transistors so that the electronic signal is stored in the fourth capacitor.

6. (Withdrawn) The imaging system according to claim 3, the imaging system further comprising a transmitter that transmits an x-ray beam that is received by the input device so that the electronic signal represents an x-ray image taken of a human body.

7. (Withdrawn) The imaging system according to claim 6, further comprising the transmitter being synchronized to a switching of the control signals to the two-dimensional array of pixels.

8. (Withdrawn) An imaging system, comprising:

a two-dimensional array of pixels;

an input device that includes a pixel device which further includes a sensor that provides an electronic signal that represents a multi-color image or an x-ray ~~to the image to the~~ two-dimensional array of pixels, the sensor being a multi-color sensor or an x-ray sensor;

a first capacitor that ~~stores the electronic signal provided by~~ is selectively connected to the sensor;

a second capacitor that ~~stores the electronic signal provided by~~ is selectively connected to the sensor; and

a controller that selectively stores the entirety of the electronic signal provided by the sensor in either the first capacitor or the second capacitor;

the pixel device further comprising a third and fourth capacitor connected to the sensor; and

a plurality of transmitters that transmit different optical images onto the two-dimensional array of pixels, or which illuminate different attributes of an object whose image lands on the two-dimensional array of pixels.

9. (Withdrawn) The imaging system according to claim 8, ~~further comprising wherein~~ the plurality of transmitters are synchronized to a switching of the control signals to the two-dimensional array of pixels, such that one attribute is stored in the first capacitor, and another attribute is stored in the second capacitor.

10. (Withdrawn) The imaging system according to claim 9, ~~further comprising wherein~~ the different attributes of the object ~~being~~ are different colors.

11. (Withdrawn) An imaging system, comprising:  
a two-dimensional array of pixels;  
an input device that includes a sensor that provides an electronic signal that represents a multi-color image or an x-ray to the ~~image~~ two-dimensional array of pixels, the sensor being a multi-color sensor or an x-ray sensor;

a first capacitor that ~~stores the electronic signal provided by~~ is selectively connected to the sensor;

a second capacitor that ~~stores the electronic signal provided by~~ is selectively connected to the sensor;

a controller that selectively stores the entirety of the electronic signal provided by the sensor in either the first capacitor or the second capacitor;

the pixel device further comprising a third and fourth capacitor connected to the sensor; and

a readout scheme which resets a voltage across the first and second capacitors to different values, such that the sensor is sensitive to different attributes of the image due to a changed voltage across the sensor.

12. (Withdrawn) An imaging system, comprising:

a two-dimensional array of pixels;

an input device that includes a sensor ~~which~~ that provides an electronic signal that represents a multi-color image or an x-ray an image to the two-dimensional array of pixels, the sensor being a multi-color sensor or an x-ray sensor;

at least one transistor connected to the sensor;

a controller that provides control signals and that selectively stores the entirety of the electronic signal provided by the sensor in either ~~the~~ a first capacitor or ~~the~~ a second capacitor,

                    the electronic signal is stored in the first capacitor during a phase of one control signal, or is not stored in the first capacitor during a phase of another control signals.

13. (Withdrawn) The imaging system according to claim 12, the two-dimensional array of pixels further comprising:

a plurality of transistors, one of the control signals controlling one of the plurality of transistors so that the electronic signal is stored in the first capacitor during the phase of the one of the control signals, and another one of the control signals controlling

another one of the plurality of transistors so that the electronic signal is not stored in the first capacitor during the second phase of the another one of the control signals.

14. (Withdrawn) The imaging system according to claim 12, the imaging system further comprising a transmitter that transmits an x-ray beam that is received by the input device so that the electronic signal represents an x-ray image taken of a human body, where the transmission of the x-rays are synchronized to the control of the two-dimensional array of pixels.

15. (Withdrawn) The imaging system according to claim 13, further comprising the controller controlling the electronic signal based on color features within the electronic signal so that one color of the electronic signal is stored in the first capacitor, and another color of the electronic image is not stored in the first capacitor.

16. (Withdrawn) The imaging system according to claim 13, wherein by not storing the electronic signal in the first capacitor, storage of sensor leakage current in the first capacitor is prevented.

17. (Withdrawn) An imaging system, comprising:  
a two-dimensional array of pixels;  
an input device that includes a sensor ~~which~~ that provides an electronic signal that represents a multi-color image or an x-ray ~~an~~ image to the two-dimensional array of pixels, the sensor being a multi-color sensor or an x-ray sensor;

at least one capacitor; and  
a controller that provides a first and second control signal,  
the electronic signal controlled by the controller so that the electronic signal is either added to the at least one capacitor when a phase of the first control signal is high and a phase of the second control signal is low, or the electronic signal is subtracted from the at

least one capacitor when a phase of the first control signal is low and a phase of the second control signal is high.

18. (Currently Amended) An imaging system, comprising:
- a two-dimensional array of pixels;
  - an input device that includes a pixel device which further includes a sensor that provides an electronic signal that represents a multi-color image or an x-ray ~~an image~~ to the two-dimensional array of pixels, the sensor being a multi-color sensor or an x-ray sensor;
  - at least one transistor connected to the sensor;
  - a first capacitor that ~~stores the electronic signal provided by~~ is selectively connected to the sensor;
  - a second capacitor that ~~stores the electronic signal provided by~~ is selectively connected to the sensor; and
  - a controller that:
    - controls the electronic signal that represents the image provided by the sensor; and
    - selectively stores the entirety of the electronic signal that represents the image in either the first capacitor or stores the entirety of the electronic signal that represents the image in the second capacitor.